



U.S.-Mexico Fuel Switching Demonstration on Ocean Going Vessels in the Gulf of Mexico and Implications for ECA

Angela Bandemehr

U.S. EPA

Office of Global Affairs and Policy

Karen Riggs, Battelle, Presenter



Harbors, Navigation, and Environment
Seminar

San Francisco, CA

May 1 – 3, 2012

Background

Contribution of shipping to PM_{2.5} concentrations (in $\mu\text{g}/\text{m}^3$)



Worldwide Ship
PM-Related
Mortality

Source: Corbett, James J., James J. Winebrake, Erin H. Green, Prasad Kasibhatla, Veronika Eyring, Axel Lauer, "[Mortality from Ship Emissions: A Global Assessment](#)," *Environmental Science & Technology*, 41(24), December 15, 2007, pp. 8512-8518.


Project Partners

- Port of Houston Authority
- U.S. Maritime Administration
- Mexican Ministry of Environment/PEMEX
- Maersk Line/Hamburg Süd
- ICF, University of California at Riverside, and Battelle


Project Goals

- Demonstrate Switching to Low Sulfur Distillate Fuels in Gulf of Mexico
- Measure Emission Reductions
- Estimate Emission Reductions at Mexican Ports from Fuel Switching
- Estimate Health and Environmental Benefits from Fuel Switching
- Raise Awareness of upcoming Emission Control Area


North American Emission Control Area



Caribbean ECA




MARINE VESSEL EMISSIONS (CEC 2002*)




* Source: Wang, C., J.J. Corbett, and J. Firestone. 2007. Modeling energy use and emissions from North American shipping: Application of the ship traffic, energy, and environment model. *Environ. Sci. Technol.*, 41 (9), 3226-323

2020 Potential ECA PM_{2.5} Reductions



2020 Potential Sulfur Deposition Reductions

Improvements
in deposition
for marine and
terrestrial
ecosystems



Project Design

- Demonstration of fuel switching on two ocean going vessels of Maersk and Hamburg Süd
 - Fuel switched from high sulfur heavy fuel oil (>3.0% sulfur) to marine gas oil (< 0.1% sulfur)
- Stack emission monitoring
- Modeling – Port emission inventories, air quality, loadings

Maersk Demonstration



- Maersk Roubaix
 - Container Ship – 1118 TEUs
 - 9.7 MW Propulsion Engine
 - Medium Speed Engine
- Switched from Bunker Fuel (3.3% Sulfur) to Distillate Fuel (0.14% Sulfur) 24 nm from shore at Port of Houston and Port of Progreso, Mexico
- Calculated Emission Reductions per call at Progreso
 - 27 kg NO_x (7%)
 - 47 kg PM_{2.5} (81%)
 - 479 kg SO_x (88%)
 - 2% increase in operating costs

Hamburg Süd Demonstration



- Cap San Lorenzo
 - Container Ship – 3,739 TEUs
 - 28.8 MW Propulsion Engine
 - Slow Speed Engine
- Represents 40% of container ships and 20% of all ships calling on Veracruz and Altamira
- Stack emissions measured in port and at sea at Altamira, Veracruz and Houston

Observed Operational Findings

- No significant issues encountered
- No additional training needed for crew involved in this demonstration
- Cost and Availability of Low Sulfur Fuel
 - Additional cost for fuel switch represents less than 2% of voyage costs
 - Demonstration fuel available in U.S.
- Tank Size
 - Sufficient capacity to carry MGO for demonstration
- Fuel Switching Procedure
 - Boilers must be slowly turned down
 - Switch over took about an hour

Emission Sampling


- Measurements of in-use stack emissions and their reduction from fuel switching
 - MARPOL NOx Technical Code (NTC) and other protocols
 - Specific engine loads and transient operations, main and auxiliary engines




Pollutants measured

- NOx, CO, CO₂ continuously
- PM continuously and speciated PM (EC, OC) with discrete filter samples
- Measure SO₂ and calculate SOx from fuel measurements

Propulsion Engine Results – SO₂




Propulsion Engine Results – PM_{2.5}




Fuel Switching Emissions

HFO -> MGO





Reductions from Fuel Switching in Port of Veracruz

With 24 nm Boundary




Emission Inventory based on 2005 activity data

Veracruz Emissions by Ship Type



Effect of Fuel Switching Zone Size for Port of Veracruz



Dispersion Modeling

Estimated Annual Total Deposition of SO₂ to Reefs in Veracruz

Reef		Units	HFO	MGO	Difference	Percent Reduction
Reef Area 1	Area	m ²	283,474,477			
	Total Annual SO ₂ Flux	g/m ²	0.19	0.01	0.18	
	Total Annual Deposition	kg	53,000	1,900	52,000	96%
Reef Area 2	Area	m ²	57,673,276			
	Total Annual SO ₂ Flux	g/m ²	0.0093	0.00081	0.008	
	Total Annual Deposition	kg	540	47	490	91%
Total	Total Annual SO₂ Deposition	kg	54,000	2,000	52,000	96%

Raising Awareness

- Meetings and Workshops
 - Mexico City
 - Veracruz
 - U.S. Gulf States
- Aquarium Kiosk - Video
- Press Releases
- Web site
- Final Report



www.epa.gov/international/fuelswitch.html

Summary

- Fuel switching can significantly reduce PM and SOx emissions
- Fuel switching within 24 nm reduces annual emissions of PM by 78% and SOx by 87% at the Port of Veracruz
- Deposition of SOx on sensitive reefs around Veracruz reduced by 52 Metric Tonnes per year (96%)
- Final Report available at <http://www.epa.gov/international/fuelswitch.html>

Outcomes

- Awareness of North American ECA and implications for Mexico
- Initiating technical studies needed to determine impacts of an ECA on Mexican public health and environment, if Mexico were to adopt an ECA